

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

CLEAN VERSION

1

METHOD FOR SYNCHRONIZING CYLINDERS IN TERMS OF QUANTITIES OF
FUEL INJECTED IN AN INTERNAL COMBUSTION ENGINE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a U.S. national stage application of
International Application No. PCT/EP2005/050428 filed
February 1, 2005, which designates the United States of
5 America, and claims priority to German application number
DE 10 2004 006 554.3 filed February 10, 2004, the contents of
which are hereby incorporated by reference in their entirety.

TECHNICAL FIELD

10 The invention relates to a method for synchronizing,
between the cylinders of an internal combustion engine, the
differences in the quantity of fuel injected. According to
this method, the differences in the quantity of fuel injected
which exist at an operating point in the lower engine-speed
15 range with the injection parameter values valid at that point
under normal operating conditions are determined by means of a
method of measuring individual cylinders to record the
irregularity in the running of the internal combustion engine
and, having been assigned to the low operating point, are
20 learned. Also, according to this method, for operating ranges
with higher loads and engine speeds, an adaptation of the
differences in the quantity of fuel injected is carried out
for a chosen injection parameter.

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

CLEAN VERSION

2

BACKGROUND

A method of this type is already known from
DE 197 00 711 A1.

In a multi-cylinder internal combustion engine, a
5 systematic error in the injection of fuel into the combustion
chambers arises as a result of variances, in particular in the
mechanical properties of the injection device, for example of
the injectors in diesel engines with a common-rail injection
system. Due to manufacturing tolerances of the said components
10 and differing degrees of wear (ageing effects), differing
quantities of fuel are fed for combustion in the individual
cylinders in identical injection periods and under otherwise
identical boundary conditions. The differing quantities of
fuel lead to a differing output of power by the individual
15 cylinders which, as well as increasing the irregularity in the
running of the engine, also leads to an increase in the
quantity of harmful exhaust-gas components.

It is known for the irregularity in the running of an
internal combustion engine to be analyzed in order to draw
20 conclusions therefrom as to the quantity of fuel injected in
the various combustion chambers. For this purpose, for example
the angular acceleration of the crankshaft is measured with an
engine-speed sensor, said angular acceleration depending on
the quantity of fuel injected in each case. Thus a large
25 quantity of fuel injected in the combustion cycle concerned
causes a correspondingly large angular acceleration of the
crankshaft, whereas a small quantity of fuel injected results
in only a correspondingly reduced angular acceleration. This

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

CLEAN VERSION

3

irregularity in the running of the engine is countered in known internal combustion engines by adjusting the quantities of fuel injected in the individual combustion chambers in relation to one another through appropriate activation of the various injectors. In this process, the control signals for the various injectors are altered until such time as all the cylinders make the same contribution to the torque, which indicates that a uniform quantity of fuel is being injected in the various combustion chambers.

10 This known regulation of irregularities in the running of the engine for synchronizing cylinders in terms of the quantities of fuel injected is restricted in application to low load levels under stationary operating conditions, for example idling. Braking or accelerating, as typically occur in higher operating ranges, could be interpreted incorrectly by the speed sensor on the crankshaft as a difference in the quantity of fuel injected.

15 The restriction to a low operating point for determining differences in quantities of fuel injected is, however, problematical, since these vary with at least one of the injection parameters, e.g. injection pressure and injection period. The differences in quantities of fuel injected that are determined at a low operating point cannot therefore be used for synchronizing over the whole operating range, e.g. as global correction factors for an activation parameter of the injectors, but have to be adapted to the injection parameters applicable at higher operating points. However, due to the aforementioned requirement for stationary operating conditions

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

CLEAN VERSION

4

for regulating irregularities in the running of the engine,
this is not possible without further action.

In the above-mentioned DE 197 00 711 A1, in which
correction factors for individual cylinders are applied to the
5 injection period in order to synchronize the cylinders in
terms of the quantity of fuel injected, it is proposed that
the correction factors determined at a low operating point be
adapted by an adaptation factor $f(p,t)$, which is dependent on
the injection parameters of pressure and injection period, for
10 higher operating ranges. The values of this adaptation factor
are to be stored in an engine characteristics map and taken
therefrom for adaptation of the correction factors during
operation. While the known method prevents adaptation when
the operating conditions are not stationary, it does so only
15 with the aid of a predetermined engine characteristics map
whose values cannot optimally match the dependency conditions
of the differences in the quantity of fuel injected which
exist in reality and which change over the service life of the
vehicle.

20

SUMMARY

The object of the invention is to indicate a method of
the type stated in the introduction which allows the actual
injection-parameter-dependent systematic error in terms of
25 quantities of fuel injected to be determined in a simple
manner with a view to cylinder synchronization.

According to the invention, in a generic method the
chosen injection parameter is set at the low operating point

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

CLEAN VERSION

5

for adaptation to a value which deviates from the value applicable at that point under normal operating conditions. Normal operating conditions are understood to mean that e.g. at low loads corresponding low injection pressures apply. By contrast, normal operating conditions are deviated from if e.g. at low loads high injection pressures apply. The differences in the quantity of fuel injected can then be determined for this set injection parameter value by measuring the irregularity in the running of the engine and can be learned as adaptation values assigned to the respective injection parameter value. During this adaptation, care must be taken to ensure that the movement of the operating point which can change with the injection parameter value set in each case is limited, since a changed injection parameter value would otherwise express itself in a braking or acceleration that was not initiated by the driver of the vehicle, at any rate in a new operating point, i.e. in non-stationary conditions during the adaptation process.

A particularly preferred embodiment of the method is one in which, to limit the movement of the low operating point during adaptation, at least one second injection parameter is set such that the operating point remains at least approximately stationary. This can advantageously be achieved in that, when the injection pressure, chosen as an injection parameter, is adapted to successively higher values in order to limit the movement of the low operating point, a correspondingly shorter injection period is set in each case. The second or further injection parameters are controlled here

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

CLEAN VERSION

6

as auxiliary variables such that the driver does not notice the adaptation process at all. Since just a few piston strokes are sufficient for adaptation, the engine control can also without further action be set such that the driver cannot
5 cancel the stationary conditions during the critical adaptation phase, or only where a threshold is exceeded in the desired output requested by the driver via the throttle.

All embodiments of the inventive method provide the advantage that a low operating point can be selected for
10 adaptation, at which the maximum sensitivity and/or reliability of measurement of the irregularity in the running of the engine is achieved, although a correct adaptation is made for high operating ranges. In particular, the low operating point can be chosen in the idling range.

15 The adaptation values learned serve to calculate correction factors for individual cylinders, by means of which correction factors, generally as part of the regulation of the irregularity in the running of the engine during the adaptation process and under operating conditions, an
20 activation parameter of an injection device of the internal combustion engine is applied such that a synchronization of the quantities of fuel injected occurs.

It has proven to be advantageous in this respect for the injection device for each cylinder to be formed by an injector
25 with a piezoelectric actuator, the activation energy of the actuators being used as an activation parameter. The actuator deviation necessary for synchronization can thus be adapted, in particular for different injection pressure values.

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

CLEAN VERSION

7

In order to record the irregularity in the running of the internal combustion engine, the angular acceleration of the crankshaft of the internal combustion engine caused by the differing quantities of fuel injected in individual cylinders can be analyzed. The determination of adapted differences in the quantity of fuel injected or of adapted correction factors for synchronization can consequently be based upon very accurate measurement methods.

The inventive method also opens up the possibility that at the stationary operating point set for adaptation with synchronized quantities of fuel injected, the absolute value of the associated quantity of fuel injected is determined from a stored model of the torque of the internal combustion engine. Diagnosis of the absolute value of the quantity of fuel injected is vital for compliance with limits on exhaust emissions, particularly where the diagnosis of small injection quantities, especially of pre-injection quantities, which lie in the region of a few milligrams, is concerned.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention is described in detail below with the aid of the schematic drawings, in which:

Figure 1 shows a flow diagram of the implementation of the method of synchronizing quantities of fuel injected according to the invention,

Figure 2 shows a flow diagram of the implementation of the preferred method of synchronizing quantities of fuel injected by adapting the loading time.

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

CLEAN VERSION

8

DETAILED DESCRIPTION

After the start 1 of the synchronization of injection quantities, an initialization phase 2 is provided as the next step, in which the adaptation values stored in an earlier
5 diagnostic cycle are loaded into an engine control device (not shown). The initialization of a new diagnostic cycle can take place both after each starting of the internal combustion engine and after certain predeterminable time or maintenance intervals.

10 After the end of initialization 2, the checking of the activation conditions occurs in a passive diagnosis step 3. Here, it is a matter of waiting until preferred operating conditions have been reached for adaptation to a normal injection parameter value or one that deviates therefrom.

15 These include, for example, the load, the engine speed or the coolant temperature. The engine control will optionally have to be adjusted so that in the subsequent adaptation process the dynamics of the change over time of the operating point sought for implementing the adaptation cycle are limited.

20 As soon as the activation conditions are fulfilled, the actual active diagnosis cycle 4 is started. Firstly, a regulation of the irregularity 6 in the running of the engine is carried out with the normal injection parameters 5 associated with the engine operating state (cf. set of
25 injection parameters in Figure 1). As a result, the quantities of fuel injected by the individual injectors of the internal combustion engine at the preferred low operating point are synchronized with one another. There is, on the other hand,

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

CLEAN VERSION

9

also the additional opportunity for analyzing at this point in the process that at the preferred low operating point with the predetermined normal injection parameter values an injection quantity that is known from the torque model will be decided
5 upon which, according to the torque achieved, must apply.

Thereafter, in step 7 (adaptation of activation parameters), further injection parameters or injection parameter sets i are loaded and, for this purpose, regulation of the irregularity in the running of the engine is carried
10 out in each case, comprising a determination of the differences in the injection quantity prevailing at the set value of the chosen injection parameter or comprising synchronization by means of appropriate correction factors for an activation parameter. For adaptation, a suitable activation
15 parameter such as, for example, the energy fed to the actuators, is selected. The resulting adaptation values are assigned to the injection parameter set, i.e. primarily to the injection parameters such as e.g. injection pressure and injection period, whose influence on the differences in the
20 quantity of fuel injected is to be maintained, assigned and stored in order that they can be called up later, when operating with higher loads and engine speeds and the associated normal values of the chosen injection parameter, for directly synchronizing quantities of fuel injected without
25 a diagnostic cycle. If the adaptation was carried out for a sufficiently large number of checkpoints (typically from five to ten), i.e. for example for all $i=1$ to $i=k$ injection parameter values of the pressure, the end 8 of the adaptation

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

CLEAN VERSION

10

or of the current diagnostic cycle is reached and the stored adaptation values can be used under operating conditions for synchronizing the quantities of fuel injected.

It has emerged that the differing injection quantities of
5 injectors, which injection quantities are dependent on the injection period, can be synchronized with one another in a simple manner by changing the displacement of the actuators. This means, for example, that for various injection pressures chosen as injection parameter values, an adaptation of the
10 actuator displacement is carried out. On the other hand, the activation energy used as an injector control variable can of course also be used for varying the start of injection.

In each diagnostic cycle, the adaptation values or correction factors last stored are overwritten by the newly
15 determined ones, as a result of which account is taken in particular of the ageing effects of the injection device that have occurred in the meantime and which will possibly lead to changed variances with regard to the quantities of fuel injected into the various combustion chambers.

20 The method shown in Figure 2 implements in step 11 an initialization. In this step, the stored adaptation values are loaded. In step 12, a check is carried out as to whether the activation conditions are fulfilled, i.e. whether constant operating conditions such as e.g. constant load, constant
25 engine speed, constant temperature of the coolant, etc. apply. In this way, the diagnosis remains passive, as shown in step 13, until in step 12 the activation conditions are fulfilled. Then in step 14, the process continues whereby the injection

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

CLEAN VERSION

11

parameters for an initial loading/unloading time are loaded.
The initial loading/unloading time can in this way be set to
200 μ s, for example. The injection parameters include
injection pressure, injector energy, type of injection, i.e.
5 whether it is a pre-injection, main injection or post-
injection. Once these parameters are loaded, then in step 15
the process continues to regulation of the irregularity in the
running of the engine. The regulation of the irregularity in
the running of the engine is carried out cylinder-selectively,
10 i.e. for a four-cylinder engine, for example, cylinder no. 1
is regulated first. Once the injection parameters are set for
the injector of cylinder no. 1, then the injector of the
second cylinder follows. The regulation can set the
loading/unloading time, the injection pressure, the activation
15 energy and the type of injection. In special cases, the
regulation can be carried out for a defined (fixed) activation
period (injection period) and defined (fixed) injection
pressure, the actuator energy being adapted accordingly. At a
rail pressure of, for example, 1500 bar and an injection
20 quantity of 0.84 mg, activation times of less than 160 μ s have
to be implemented.

In step 16, a check is carried out to ascertain whether
with these variables the irregularity in the running of the
engine lies below a threshold value S. If this is not the
25 case, then in step 17 the activation period must also be
changed. This is necessary in particular in the case of
"badly" manufactured injectors which cope badly with these
short loading/unloading times, if at all. With such injectors

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

CLEAN VERSION

12

and short unloading times, the fuel quantity injected is independent of the actuator energy. A type of "quantity saturation" sets in and the quantity of fuel injected can no longer be changed by increasing the actuator energy. This
5 means that the adaptation of injections in a defined operating state must not be carried out solely by adapting the energy but by extending the activation period, which consequently prolongs the injection period.

As a result of successfully regulating the irregularity
10 in the running of the engine after step 16, the quantities of fuel injected by the individual injectors are synchronized with one another. These injection parameters are stored for the associated loading/unloading time τ_i (step 18). A check is carried out in step 19 as to whether the loading/unloading
15 time τ_i is greater than or equal to an extreme value. The extreme value here stands, for example, at 140 μs . In the above example, the initial value τ_0 lies at 200 μs . It should be noted that the index i here is equal to zero. Since the condition established in step 19 is not fulfilled, the process
20 continues in step 20. Before the next set of parameters is loaded in step 14 the loading/unloading time is first reduced by 10 μs in step 20. Consequently, the loading/unloading time τ_1 now equals 190 μs . In step 21, only the index is increased by 1. The existing injection parameters for τ_1 are now loaded
25 in step 14. As already described above, the steps 15 to 19 then follow. When all the sets of parameters are adapted for the various loading/unloading times, the constant injection pressure (e.g. 1500 bar) can be set to a different new

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

CLEAN VERSION

13

constant injection pressure (e.g. 1400 bar). As soon as the new pressure is applied in step 12, the actuator energy for every loading/unloading time from 200 to 140 μ s is determined according to steps 14 to 19. This can be carried out for
5 various pressure values. As soon as a sufficiently large number of measurement values are available, the method ends in step 22. It should be noted that the gradual changing of the loading/unloading time by 10 μ s in step 20 was given only by way of example. For more refined modeling, differences of 1 μ s
10 from one loading/unloading time to the next loading/unloading time are entirely conceivable. This inventive diagnosis can be implemented very quickly since just a few piston strokes suffice.

In summary, the inventive method makes it possible for
15 the diagnosis of differences in the quantity of fuel injected or of the injection quantity itself to be carried out at a preferred low operating point at which the maximum sensitivity and reliability of regulation of the irregularity in the running of the engine exists. At this operating point, the
20 diagnosis and adaptation then also take place for injection parameter values which are valid under operating conditions for other operating points. Thus, at the low operating point both a synchronizing of the injection quantity differences between the individual injectors and a calibration of the
25 injection quantity to the pertinent values of the selected injection parameter set artificially in the diagnostic cycle occur, an unwanted movement of the adaptation operating point being prevented or limited by the contrary setting of other

ATTORNEY DOCKET NO.
071308.0746
2003P13891WOUS

PATENT APPLICATION

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

CLEAN VERSION

14

injection parameter values. The synchronizing of quantities of fuel injected through regulation of the energy of the injector activation parameter depending, in particular, on the injection parameter of pressure, is preferred.

5 Optionally, it is possible at the set operating point, based on knowledge of the engine operating state (temperature of coolant, active consumers) to read out from the torque model the absolute value of the injection quantity and to use it, for example, for the exact calibration of the injection
10 quantity/injection period characteristics map.